

MECHANICAL CLEANING RENZORATO

THE FLEXIBLE NEW WAY OF DRAIN CLEANING

The new **Renzorato** high-speed flexible shaft drain cleaning machine has been designed for the rapid removal of rust, cement, lime, and small tree roots in concrete, cast iron and PVC drains up to 150 mm. Producing up to 3,000 RPM, the high rotation speed means the specialised selection of tools covers every part of the drain wall for thorough cleaning. This makes the machine ideal for sewer cleaning, CIPP preparation and cutting applications. The spring is protected with a flexible outer cover that allows the cable to go through the tightest of bends. The **Renzorato** can be supplied with a range of specialist cleaning heads for optimal operation in different drain types and diameters.



38 - 150 mm



8 mm
(12 mm cover),
10 mm
(15 mm cover)



20 m



35 kg

Talk to the experts **1800 028 584** or visit us online seca.com.au

FLEXIBLE SHAFT DRAIN CLEANER

The electric engine pack and the reel can be separated and used independently. It is also possible to work with a separate cable and the detachable engine pack. Because the **Renzorato** uniquely separates into two components, transportation and lifting is a simple and safe task.

Remote Control

The **Renzorato** is the only high-speed flexible shaft machine in its class supplied with adjustable radio remote control. The ergonomic design means the unit excels in confined spaces, with the hand-operated remote control enabling comfortable and safe operation a few meters away from the machine.

Using the remote control, the maximum speed and torque can be set gradually, depending on the nature of the task and pipe material, helping minimize the risk of damage. The LED display also shows the torque and speed of the cleaning head as it progresses along the pipe, giving a clear indication of the effectiveness of your cleaning action.

Drive

The **Renzorato** is powered by a muscular 0.55 kW electric motor. This specially developed engine is both quieter and more powerful than drives made for common hand tools, such as angle grinders or drills.

Transportation

The **Renzorato** is mounted on two wheels and includes a retractable handle for ease of transportation. When working in confined spaces or difficult to reach areas, such as an apartment block without an elevator, the electric engine pack and the reel can be separated and used independently. It is also possible to work with a separate cable and the detachable engine pack. Because the **Renzorato** uniquely separates into two components, transportation and lifting is a simple and safe task.

Interchangeable Reels

The **Renzorato**'s detachable engine pack can be used with different reel combinations. Available reel lengths and cable diameters include:



CONFIGURATIONS				
	Cable	Cable Housing	Length	Pipe Diameter
Renzorato1 - Small Reel	8 mm	12 mm	15 mtrs	38 - 100 mm
Renzorato2 - Small Reel	10 mm	15 mm	12 mtrs	50 - 150 mm
Renzorato - Large Reel	10 mm	15 mm	20 mtrs	50 - 150 mm

TECHNICAL SPECIFICATIONS	
Motor	0.55 kW
Ø Operating range	38 - 150 mm (90° bends as from 40 mm)
Ø Spring/cover	8 mm / 12 mm and 10 mm / 15 mm
Length 8 mm spring	15 m
Length 10 mm spring	12 metres or 20 metres (larger reel)
Weight	35 kg total (engine 17 kg, reel 18 kg)



Accessories

A large number of accessories are available for **Renzorato**. Choose the desired accessory depending on the pipe construction and application. Chain heads with carbide tips are available for cast iron and concrete pipes. Smooth chain heads are available for cleaning and unclogging PVC pipes. There are also different drill heads available for the toughest jobs.