

# T- Handle Gripper

Part Number	Nominal Size	Range of Use	Maximum Back Pressure	Length	Product Weight	Bypass Diameter (NPT)	
<b>T-Handle Gripper with Bypass</b>							
272949	<b>6"</b> (150 mm)	5.7"-6.3" (144-160 mm)	17 psi (1,2 bar)	40 ft. (12 M)	9.7" (247 mm)	6.5 lbs (3 kg)	1/4" M
272957	<b>8"</b> (200 mm)	7.7"-8.3" (196-211 mm)	17 psi (1,2 bar)	40 ft. (12 M)	9.7" (247 mm)	9.5 lbs (4.3 kg)	3/4" M
272965	<b>10"</b> (250 mm)	9.8"-10.3" (248-262 mm)	17 psi (1,2 bar)	40 ft. (12 M)	9.7" (247 mm)	12.5 lbs (5.7 kg)	3/4" M
272973	<b>12"</b> (300 mm)	11.7"-12.3" (297-312 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	9.7" (247 mm)	16 lbs (7.3 kg)	3/4" M
272981	<b>15"</b> (380 mm)	14.8"-15.3" (377-388 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	9.7" (247 mm)	24 lbs (10.7 kg)	3/4" M
272998	<b>18"</b> (460 mm)	17.7"-18.3" (450-465 mm)	8.7 psi (0,61 bar)	20 ft. (6.1 M)	9.7" (247 mm)	31 lbs (14 kg)	3/4" M
<b>T-Handle Gripper</b>							
272892	<b>6"</b> (150 mm)	5.7"-6.3" (144-160 mm)	17 psi (1,2 bar)	40 ft. (12 M)	9.7" (247 mm)	6 lbs (2.7 kg)	
272906	<b>8"</b> (200 mm)	7.7"-8.3" (196-211 mm)	17 psi (1,2 bar)	40 ft. (12 M)	9.7" (247 mm)	9 lbs (4.1 kg)	
272914	<b>10"</b> (250 mm)	9.8"-10.3" (248-262 mm)	17 psi (1,2 bar)	40 ft. (12 M)	9.7" (247 mm)	12 lbs (5.4 kg)	
272922	<b>12"</b> (300 mm)	11.7"-12.3" (297-312 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	9.7" (247 mm)	15.5 lbs (7 kg)	
272930	<b>15"</b> (380 mm)	14.8"-15.3" (377-388 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	9.7" (247 mm)	23 lbs (10.4 kg)	
272888	<b>18"</b> (460 mm)	17.7"-18.3" (450-465 mm)	8.7 psi (0,61 bar)	20 ft. (6.1 M)	9.7" (247 mm)	30 lbs (13.6 kg)	

Always block plugs when conducting air tests.

Mechanical Plugs



VISIT US ONLINE [seca.com.au](http://seca.com.au)