

## ENZ HRH Semi Radially Rotating Nozzles Backwards: Working pressure up to 280 bar

Part #	Thread	Rotating Nozzles	Thrust Nozzles	Applicability from dia.	Measures	Weight	min. l/min at 100 bar
02.028A	1/4"	4x M4	without	30-100mm	ø28 x 60mm	200g	8
02.028B	3/8"	4x M4	without	30-100mm	ø28 x 60mm	200g	8
02.028AS	1/4"	4x M4	3x M4	30-100mm	ø28 x 60mm	200g	12
02.040A	1/2"	4xM6	without	70-150mm	ø40 x 83mm	550g	16
02.040B	3/4"	4xM6	without	70-150mm	ø40 x 83mm	550g	16
02.040AS	1/2"	4xM6	3xM6	70-150mm	ø40 x 83mm	550g	20
02.050A	1/2"	4xM6	without	100-200mm	ø50 x 100mm	1.10kg	40
02.050B	3/4"	4xM6	without	100-200mm	ø50 x 100mm	1.10kg	40
02.050AS	1/2"	4xM6	3x M6	100-200mm	ø50x100mm	1.10kg	40
02.050BS	3/4"	4xM6	3x M6	100-200mm	ø50x100mm	1.10kg	40
02.060	1"	4x M8	3x M8	100-300mm	ø60x118mm	1.60kg	60
02.100A	1"	4x M10	3x M10	100-600mm	ø100x180mm	7.40kg	200
02.100B	1" 1/4"	4x M10	3x M10	100-600mm	ø100x180mm	7.40kg	200