

ENZ KBR ROTATING COMBI NOZZLES: Working pressure up to 280 bar

This rotating nozzle is fitted with 2 spinning jets set at 90° and 2 semi radial rotating jets set at 45°. This combination allows, positive forward thrust and flushing of the debris as well as cleaning of the pipe wall and pipe joints.

Part #	Thread	Rotating Nozzles	Thrust Nozzles	Applicability from dia.	min. l/min at 100 bar
04.011A	1/16"	2x0.8/2x0.9	without	12-30mm	10
04.011B	1/16"	2x0.8/2x0.9	without	12-30mm	10
04.012	1/8"	2x0.8/2x0.9	without	13-30mm	10
04.016A	1/8"	4x 0.7-1.1	without	18-60mm	10
04.016B	1/4"	4x 0.7-1.1	without	18-60mm	10
04.028A	1/4"	4x M4	without	30-100mm	10
04.028B	3/8"	4x M4	without	30-100mm	10
04.028AS	1/4"	4x M4	3x M4	30-100mm	10
04.040A	1/2"	4x M6	without	70-150mm	20
04.040B	3/4"	4x M6	without	70-150mm	20
04.040AS	1/2"	4x M6	3x M6	70-150mm	20
04.050A	1/2"	4x M6	without	100-200mm	70
04.050B	3/4"	4x M6	without	100-200mm	70
04.050AS	1/2"	4x M6	3x M6	100-200mm	70
04.050BS	3/4"	4x M8	3x M8	100-200mm	70
04.060	1"	4x M8	3x M8	100-300mm	80
04.100A	1"	4x M10	3x M10	200-600mm	200
04.100B	1 1/4"	4x M10	3x M10	200-600mm	200