

ENZ KBRV ROTATING COMBI NOZZLES FORWARD: Working pressure up to 280 bar

The KBRV nozzle has 2 semi radial jets directed forward at an angle of 45° and 2 nozzles set at 90° to the pipe wall. It is also fitted with 3 rear thruster nozzles to provide positive forward movement in the pipe.

Part #	Thread	Rotating Nozzles	Thrust Nozzles	Applicability from dia.	min. l/min at 100 bar
04.011AV	M7	2x0.8/2x0.9	without	12-30mm	10
04.011BV	M8	2x0.8/2x0.9	without	12-30mm	10
04.012V	1/8"	2x0.8/2x0.9	without	13-30mm	10
04.016AV	1/8"	4x 0.7-1.1	without	18-60mm	10
04.016BV	1/4"	4x 0.7-1.1	without	18-60mm	10
04.028AV	1/4"	4x M4	3x M4	30-100mm	20
04.040AV	1/2"	4x M6	3x M6	70-150mm	30
04.050AV	1/2"	4x M6	3x M6	100-200mm	70
04.050BV	3/4"	4x M6	3x M6	100-200mm	70
04.060V	1"	4x M8	3x M8	100-300mm	100
04.100AV	1"	4x M10	3x M10	200-600mm	200
04.100BV	1 1/4"	4x M10	3x M10	200-600mm	200