

## **ENZ BULLDOG NOZZLES:** **Working pressure up to 200 bar**

| Part #   | Thread | Rotating Nozzles | Thrust Nozzles | Front Nozzles | Applicability from dia. | Measures   | Weight | min. l/min at 100 bar |
|----------|--------|------------------|----------------|---------------|-------------------------|------------|--------|-----------------------|
| 400.037  | 1/2"   | 4xM6             | 3xM6           | 1xM6          | 70-200mm                | Ø42x98mm   | 0.60kg | 50                    |
| 400.060A | 3/4"   | 4xM8             | 3xM8           | 1x M8         | 100-300mm               | Ø60x131mm  | 1.7kg  | 100                   |
| 400.060B | 1"     | 4xM8             | 3xM8           | 1x M8         | 100-300mm               | Ø60x131mm  | 1.7kg  | 100                   |
| 400.080  | 1"     | 5xM10            | 6xM8           | 1x M10        | 100-300mm               | Ø178x226mm | 3.9kg  | 100                   |
| 400.100A | 1"     | 4xM10            | 3xM10          | 1x M10        | 200-600mm               | Ø178x226mm | 7.6kg  | 200                   |
| 400.100B | 1 1/4" | 4xM10            | 3xM10          | 1x M10        | 200-600mm               | Ø178x226mm | 7.6kg  | 200                   |