



SETTING THE STANDARD FOR

AFFORDABLE QUALITY EXCELLENCE

Hathorn H7

Standard Camera System

Elevate your residential plumbing, contracting, and home inspections with a top-tier solution. Engineered to excel in diverse markets, this all in-one system boasts a seamless integration of cutting-edge features.

FEATURES INCLUDE:

- Available in 60m & 1.43 self leveling camera head
- Screenshot option function
- Internal hard drive of 64GB
- 512Hz high power sonde
- Record to USB & HDD
- 7" (17.8cm) impact resistant daylight readable LCD screen







Specifications

Display

Size & Type 17.8cm impact resistant daylight readable LCD

Resolution & Brightness 1024 x 600 pixels with 1,000 cd/m2

Recording, Storage & Features

Reading Options MPEG4 video (H.264 at 30fps) and JPEG screenshot Storage Options USB, HDD or USB and HDD **USB** Capacity USB 2.0 up to 32Gb Hard Drive Capacity 64Gb SSD English, Spanish, French Menu Languages Footage Counter Feet or meters with reset function Sonde Frequency High power 512Hz Push Rod 60M of HPDE push rod with coax core

Power

Battery Only Milwaukee M18° 18V or equivalent (not incl.)

Battery Life ~5-6hrs using 3.0Ah (when not recording & sonde off)

Battery Extender Auto dimming & auto saving

AC/DC Adapter 12V - 4.1A (included)

Weigh & Dimensions

Weight without Battery 20Kg

Dimensions (L x W X H) 84cm x 48cm x 41cm (33" x 19" x 16")

Environmental

	Water Resistance	IP65 when lid closed / IP64 when lid open
	Operating Temperature	-10°C to 50°C
	Storage Temperature	-20°C to 60°C



Catalog #	Camera	Self	Rod	Min 90°	Max. Pipe
	Head	Levelling	Length	Elbow	Well Lit
H7-2143-SL	1.43"	Yes	60m	1/2"	10"